Carpent

Draft Ne
Plan Su
Matrix o

2

14th July

Max Fordham LLP
Max Fordham LLP
42/43 Gloucester Crescent
London
NW1 7PE

T +44 (0)20 7267 5161
F +44 (0)20 7482 0329

maxfordham.com

Max Fordham LLP is a Limited Li2 9

ISSUE HISTORY

Issue	Date	Description
1	17/5/17	Draft for Comment
2	14/07/17	Final Issue

MAX FORDHAM LLP TEAM CONTRIBUTORS

Engineer	Role
Hero Bennett	Senior Sustainability Consultant
Peter Creaney	Engineer

CONTENTS

1.0 Introduction 4
2.0 Planning policy context 4
3.0 The sustainability matrix 5
3.1 What is the Max Fordham sustainability matrix? 5
3.2 Planning Policy and Draft Neighbourhood Plan matrix overlay 5
4.0 Gap analysis and conclusions based on the matrix overlay 6
4.1 Conflicting criteria 6
4.2 Neighbourhood plan: areas not fully covered 7
5.0 Recommendations 8
5.1 Recommendations for improving the Neighbourhood Plan 8
Appendix I t Policy context in detail 10
5.2 The London Plan, Spatial Development Strategy for Greater London 2011 10
5.3 London Legacy Development Corporation 11
appendix II t d Z Œ ‰ v š Œ [• • š š ^ µ • š] v] o] š Ç 3 D š Œ] Æ

In many cases the planning policy requirements do not the match the wording in the matrix word for word. In this case we have used our judgement to decide where the highlight should stop; this indicates where we feel the policy meets the aims of the target level and best aligns in our opinion.

Home Quality Mark (HQM) overlay

HQM is a new voluntary standard introduced by the BRE for residential developments as a way to ensure a level of sustainability that is monitored by a third party. Certificates can be achieved from level 1 to 5. It is significantly more comprehensive than the Code for Sustainable Homes. The matrix makes reference to the HQM requirements. This is represented as:

Requirements that corresponds to 1 credit in the relevant HQM issue

Requirements that corresponds to 2 credits in the relevant HQM issue

Sustainability Matrix neighbourhood plan overlay

d Z Œ ‰ v š Œ [• • š š Œ (š E] P Z } µ Œ Z } } W o v ~ Œ (š ð U & Œ µ Œ Ç î ì í ó • Sustainability Matrix. As shown in Figure 2 specific references made in the Neighbourhood Plan have been highlighted in blue. The final column gives the policy reference and more clarification where necessary.

The matrix is given in Section 5.0

4.0 GAP ANALYSIS AND CONCLUSIONS BASED ON THE MATRIX OVERLAY

matrix but are covered in the Neighbourhood plan. These are important elements of the sustainability story of the Neighbourhood plan and so are referenced separately below.

Z o o v Á Z}u • Á]o o Z] À Z]P Z • š v Œ • }u(ding low and zero carbon energy, v š U]v best practice in sustainable urban drainage (SuDS), the re-use and recycling of resources, and the production and consumption of renewable energy. The provision of low and zero carbon energy infrastructure in new developments will be linked to existing buildings.

Z v }µŒ P }uuµv]šÇ }Áv v ŒPÇ ‰ Œ}i š•[

5.0 RECOMMENDATIONS

5.1 Recommendations for improving the Neighbourhood Plan

- Consider stating a preference for use of the Home Quality Mark for new builds. Ratings range from 1 star to 5 stars. A 2 star rating would provide a good base level with minimising the cost impact. It should be noted that Local Authorities are no longer allowed to set requirements along these lines as part of their planning documents.
- Consider changing Lifetime Homes requirements to Category 2 Part M requirements to align with LWDC Policy BN.5: Requiring inclusive design
- It is recommended that the Neighbourhood plan changes new build energy performance standard to one of the following options:
  - CO_2 targets that align with London Plan requirements and additional fabric standards (such as targeting Best Practice Fabric Standards as set out in the Matrix)
  - Introducing an energy efficiency target for the whole dwelling based on the Standard Assessment Procedure methodology (SAP[1]) but this would incorporate fabric and systems efficiencies but would not consider low carbon delivery
  - Consider changing the wording of the EPC target for new builds Z W }Œ [Á]o o]v š Œ‰ Œ a requirement for an EPC C. In order to raise aspirations it may be better to state an EPC B is expected, and an EPC C is required as a minimum.
- For refurbished energy standards consider a combined standard of a minimum EPC standard with a elemental approach on U-values to ensure a fabric first approach

Additional work require ET BTen 1 0 0 1 92.664 474.55 Tm [<00

APPENDIX 1: POLICY CONTEXT IN DETAIL

5.2 The London Plan, Spatial Development Strategy for Greater London 2011

The London Plan: Spatial Development Strategy for Greater London published in March 2015 (consolidated with alterations since 2011) forms the statutory Development Plan and policy principles, those relevant to this report include:

London Plan Policy 5.2 Minimising Carbon Dioxide Emissions
Development proposals should follow the energy hierarchy

1. Be Lean: use less energy;
2. Be Clean: supply energy efficiently;
3. Be Green: use renewable energy.

The GLA Guidance on Preparing Energy Assessments (March 2016) states the Mayor will apply a 35% carbon reduction target beyond Part L 2013 of the Building Regulations, which is deemed broadly equivalent to 40% target set for the period of 2013-2016 in Policy 5.2 of the London Plan.

London Plan Policy 5.3 Sustainable Construction
A. The highest standards of sustainable design and construction should be achieved in London to improve the environmental performance of new developments and to adapt to the effects of climate change
B. Proposals should demonstrate that sustainable design standards are integral to the proposal
C. Major development proposals should meet the [illegible] planning guidance. The standards include measures to achieve other policies in this Plan and the following sustainable design principles:

- minimising carbon dioxide emissions across the site, including the building and services
- avoiding inter0 -26(in)-29(L)10(o/F6 9.96 T(c)-5vp)-3(o)-4(u)-3(ildiu)-3(s-5(g)] TJ E)9( )-38(th)-5(e)-33(n)-(io)-3(xid

1. Minimise internal heat generation through energy efficient design;
2. Reduce the amount of heat entering a building in summer through orientation, shading, albedo, fenestration, insulation and green roofs and walls
3. Manage the heat within buildings through exposed internal thermal mass and high ceilings;
4. Passive ventilation;
5. Mechanical ventilation;
6. Active cooling systems (ensuring they are the lowest carbon options).

London Plan Policy 5.13 Sustainable Drainage
Development should utilise sustainable urban drainage systems (SUDS) unless there are practical reasons for not doing so, and should aim to achieve greenfield run

Policy BN.8: Maximising opportunities for play

Take account of the existing or future need for play space in the local area, identifying relative deficiencies

Í0.o(n)-3(e)-D10>-8o(n6F01Atached [/h W* n BTe)-6( )-50(a)-3(c)-5(c)-5(o)-4(u)-3(n)-3(ies)] TJE03>-4-5(02>-3<)-3(>-3<)

6F Cbø™fP£Á\T3ROF Ûsq9”Ž˜¹)¹Å’›Ÿ ”&S’—KeL…t’f žÖ>=…·”‰”cæ’—K9HûéH¶lPùŸ VfG$6da`Bø™fP£Áfi tF • v rD6Sí nt ount o R